

ATN-FB

Attenuation Optical Fiber



Coractive's attenuation optical fiber (ATN) products have been specifically designed to provide flat attenuation. Wideband uniform attenuation ensures full compatibility with current and future DWDM, CATV and other telecom systems. The ATN-FB has a wide attenuation range (<15 dB/cm) for manufacturing in-line fixed attenuators used in telecommunications.

Features & Benefits

- Industry-standard fiber geometry – provides high-precision core alignment for more efficient fiber coupling
- Precise cladding diameter control – perfect ferrule fit reducing manufacturing costs & increasing production yield
- Tight attenuation tolerance – enables compatibility with DWDM network applications
- Guaranteed attenuation in 1310 nm and 1550 nm wavelength ranges
- Exceptional batch-to-batch uniformity – ensures a consistent and high-quality attenuator
- Wide attenuation range: from 0.4 to 15 dB/cm

Applications

- In-line fixed attenuators
- Telecom (DWDM, CATV)

Specifications

Optical

Core Numerical Aperture – Nominal (%)	0.14 ± 0.02
Attenuation Range* (dB/cm)	0.4 - 15
Attenuation Wavelength Range @ 1310 nm	1295 - 1325
Attenuation Wavelength Range @ 1550 nm	1535 - 1565
Attenuation Tolerance – Nominal (%)	7.5

Geometrical & Mechanical

Core Diameter (µm)	7 ± 1
Cladding Diameter (µm)	125 ± 0.5
Core/Cladding Concentricity Error (µm)	< 0.8
Coating Diameter (µm)	245 ± 10
Proof Test (kpsi)	≥ 100

Environmental

Operating Humidity (%)	5 - 85
Operating Temperature (C°)	0 - 70
Storage Humidity (%)	5 - 85
Storage Temperature (C°)	-40 - 85

ISO 9001:2015 certified quality system | RoHS and REACH compliant.
All specifications are subject to change without notice.

Reference: 100-10-0267.R2
2021.07.28

* Not all attenuations are available within given range. Please contact your sales representative for more information.

sales@coractive.com | + 1 418 845-2466

[coractive.com](https://www.coractive.com)