


SENTRYHOUND-PRO™

DUAL POLE FERROMAGNETIC SECURITY PORTAL



- Ferrous security portal beats metal detection with reduced false triggers
- Alert zones light up to pinpoint contraband PEDs (Personal Electronic Devices)
- Lightweight & simple setup in under 30 seconds
- Made entirely in the USA



+1 732-548-3737
www.bvsystems.com
sales@bvsystems.com



SENTRYHOUND-PRO™

DUAL POLE FERROMAGNETIC SECURITY PORTAL



TECHNICAL SPECIFICATIONS:

| | |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SENSORS | 8 independent sensors (4 per pole) - 1 for each zone (head/shoulders, chest/waist, thighs/knees, ankles/feet) |
| DETECTION METHOD | Passive ferromagnetic detection completely safe (no radiation emitted) for pregnant women, pacemakers & medical implants |
| DETECTION PATHWAY (TWO POLE SETUP) | Diamond-shaped motion sensor formed between bases (virtual mat isolates ferromagnetic detection to only between the 2 sensor poles) |
| SYNCHRONIZATION | IR connection & motion sensors tether poles for enhanced false trigger rejection |
| FLOW RATE | Ambient flow rate: 120 people/minute (no detection) Worst case flow rate: 25 people/minute (detection each time) |
| HORIZONTAL RANGE* | 32 to 64 inches between 2 gated sensor poles 18 to 32 inches using single sensor pole |
| VERTICAL RANGE | 75 inches (from head to toe) |
| DETECTION USE CASES | Inside visitors' bags, purses, clothing, shoes, hats, wallets, pockets, etc. Inside suitcases and other large contraband inspections |
| ALERTS | Omni-directional, daylight-bright, top dome color blinking LEDs Directional blinking color LEDs (zone specific for security personnel) Integrated siren with adjustable volume Dry trigger contacts for alarms, DVRs, video surveillance, intrusion detection systems, etc. |
| SECURITY | ON/OFF security key lock for all functions |
| SENSITIVITY | 4 levels (user selectable) |
| SETUP | Plug and play out of the box with less than 30 seconds from powering up to full operation. No software or assembly required |
| POWER | 110VAC daily operation & internal rechargeable (full charge in 3 hours) 12VDC battery (sealed gel cell) lasts over 24 hours |
| WEIGHT | 17 lbs. fully assembled (single pole) |
| DIMENSIONS | 68" H x 12" L x 8" W (fully assembled single pole and base unit) |
| OPTIONS | Wall mounting kit, hard transport case, on-site training, extended warranty |