


WIDEBAND POWER METER

- · Accurately measures digital & analog RF power
- Wide frequency range
- Measures true average power
- Touchscreen display & control
- Reads power in watts or dBm
- Reads VSWR
- Internal rechargeable battery
- Type-N connections













WIDEBAND POWER METER

FREQUENCY RANGE:	500 MHz to 4000 MHz
FREQUENCY RESOLUTION:	2.5 kHz
MEASUREMENT BANDWIDTH:	20 MHz
INPUT POWER RANGE:	from 0 dBm to 52 dBm (1 mW to 150 Watts)
MEASUREMENT RESOLUTION:	20 MHz
MEASUREMENT ACCURACY:	0.65 dB
INSERTION LOSS:	Maximum 0.4 dB
INPUT VSWR:	Less than 1.2
INPUT SIGNAL:	CW, GSM, CDMA, Wi-MAX, LTE and so on
INPUT IMPEDANCE:	50 Ohm
RUNTIME BATTERY:	4-5 Hours
STABILITY:	Temperature compensation from -10 C to 40 C degrees



YellowFrog-Pro™ includes rugged transport case, PC software, power transformer and barrel plug

OWPLAK (COM)	Deat Francis	Valuer 135	BAR ALMONDER	IDD Indexes	Battery Level	
	Core	(Inset Press)	Depise Person Press	death Person Courts	(Jackborghn)	
		11		on and a second		
Frequency: 3450.000		71				fluenced
		1.1				
NVG Count 159	<u>E</u> 1967	1.1				
	OT ADT	1	the second second	the set of the set of	a second a	
	START	-				
Note Saled	ALC: NO. OF COMPANY	7 2			10.00 March	Deschaft
© TOD. # MO	TOP STOP					
		1.1			20	
Tel agging						
FlaNoria	Distance -		a start start, much longer a	Non-contract the set out a	the same and a	

YellowFrog-Pro™ includes Windows 10 software allowing control and monitoring of all unit parameters including power over time

+1 732-548-3737 www.bvsystems.com sales@bvsystems.com

