



SiVal Instruments, Inc.

www.SiValinstruments.com

Sales@SiValinstruments.com (510) 648-1918

1777 N. Milpitas Blvd. #122, Milpitas, CA 95035 USA

MINI Projector MP720B1: \$499 Retail



The new SiVal MP720B1 Hi-Definition mini projector is the longest life projector available with its cutting-edge LED technology. High Definition LCOS projection technology helps your presentation be memorable and successful. This portable and quiet projector is suitable to watch HD movies or play games.

- 1280 x 768 HD Native Resolution – support 1080p, display up to 980,000 pixels with 16:9 (native) and 4:3 aspect ratio.
- Long Projection Life – This mercury-free LED light source has a long life up to 30,000 hours, helping to save money and avoid replacing light source. No warming up, no cooling down
- LCOS technology – Liquid Crystal On Silicon chip technology brings you life-like images and video.
- Easy Connectivity - Multiple interfaces (HDMI, VGA, CVBS) deliver high quality connectivity to laptops, desktops, DVD/Blu-Ray players, and gaming consoles. HDCP supported
- Keystone Adjustment
- Easy Usability – Easily controlled by Keypad on projector or by Remote Control
- Portable - Compact design with 5.9’’X 1.97’’ X 4.92’’ and a 1.76 pounds
- Green Device – With efficient, mercury-free LED technology, you can help protect our planet.

Panel	LCOS
Native Resolution	1280 X 768 (720P), support 1920 x 1080 (1080P)
Supported Aspect Ratio	16:9 (native), 4:3
Brightness	>50 ANSI Lumens
Contrast Ratio	200:1
Uniformity	85%
Keystone Adjustment	Auto, Vertical +/-15°
Projection Screen Size	8"-132" (0.2m ~3.35m)
Projection Distance	11.8’’ – 216.5’’ (0.3m-5.5m)
Video Input	HDMI 1.3, D-Sub, Composite. USB (JPEG only)
Audio I/O	Built-in speaker, Audio In (phone Jack), Audio line out (phone jack)
Light Source	R/G/B LED module
LED life	Up to 30,000hrs
Power Adapter	Input: AC100-240V, 50/60Hz Output: DC19V, 3A
Typical Power	30W
Size (W x D x H)	1.96’’ x 5.78’’x 5.11’’ (50mm x 147mm x 130mm)
Weight	1.96lb (0.89kg)
Operating Environment	Temperature: 5°C ~ 35°C (41°F ~ 95°F); Humidity: 80% (maximum)
Storage Environment	Temperature: -20°C ~ 60°C (-4°F ~ 140°F); Humidity: 80% (maximum)
Package Contents	1 mini-projector, 1 remote control, 1 power adapter, 1 VGA cable, 1 user manual, 1 warranty card