

## Miniature Signal Generators SG Series

The SG series of Miniature Signal Generators are supplied with control software, USB to mini USB cable and AC power supply adaptor.



\* Image Representative of Range

- 25 - 3000MHz
- Full Range Tuning
- Frequency & Level Control
- USB, Ethernet and RS-232 Interface
- External or Internal (+/-1ppm) Reference

RF Performance				
Frequency Range	25 - 3000MHz			
Frequency Step Size	100Hz			
Output Power Level	+13dBm			
Output Range	+13dBm to -17dBm, 0.5dB Steps (output level set in dBm)			
Internal Reference	100MHz, ±20ppm over temperature, ±1ppm per year (±3ppm in 1st year)			
Phase Noise Max (dBc/Hz)	Frequency	1KHz Offset	10KHz Offset	100KHz Offset
	25 - 250MHz	-98	-106	-112
	250 - 1000MHz	-92	-96	-106
	1000 - 3000MHz	-83	-94	-101
Spurious	Maximum: < -50dBc, Typical: < -70dBc			
Harmonics	Maximum: -20dBc, Typical: -25dBc			
RF Output connector	SMA Female			
Reference Connector	SMA Female Reference Input / Output autodetect and switch 100MHz Output Selectable 10 or 100MHz input (software programmable frequency) @ -4 to +12dBm			
Power				
Power Input	9 - 28V DC 12V, 3.0A AC adaptor with 1.20m lead included Current consumption: 300mA typ at 12V Can be powered also via USB3.0, current consumption: 860mA typ at 5V			
Power Selection	Automatic Switching Coaxial Power jack selected by default USB power used when coaxial power not present USB power used when coaxial power not present			

Options:  
OPT06 ASG Mounting Bracket Pair - Supplied fitted to the unit

Interface	
Control Interface	USB: Virtual COM port RS-232: 9-pin male D-sub connector Ethernet: RJ45 connector
Output Modes	Continuous Sweep On/Off via external trigger
External Trigger	Pin 4 of RS-232 connector: Pulse TTL/RS232 levels, 50ms min. pulse width Manual trigger via GUI
Status Indicators	Power Lock RF Output Reference Out
PC User Interfaces	Third-part terminal application (e.g. HyperTerm): • ASCII commands  Graphical User Interface Executable File: • Adjust frequency and output power level • Set reference frequency • Select operation mode • Set power-on defaults • Adjust sweep configuration • Change device network settings • Control multiple units
Internal Memory	Non-volatile, automatically stores most recent settings
Environmental	
Operating Temperature	-20 to +50C
Storage Temperature	-40 to +85C
Mechanical	
Dimensions	163mm x 103mm x 30.5mm
Weight	350g
Material	Aluminium extrusion Aluminium endplates with black legend Rubber Feet

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.  
Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

